

APPENDIX D6

1911 Single Stack Division

1.	Minimum power factor for Major	165
2.	Minimum power factor for Minor	125
3.	Minimum bullet weight	No
4.	Minimum bullet caliber / cartridge case length	9mm (0,354") / 19mm (0,748")
5.	Minimum bullet caliber for Major	10mm (0,40")
6.	Minimum trigger pull (see Appendix F2)	Ne
7.	Maximum handgun size	Yes. See # 20 bellow
8.	Maximum magazine length	See # 20 and # 24 bellow
9.	Maximum ammunition capacity (Does not include a chambered round)	Yes. Maximum after start signal: Major PF - 8 rounds Minor PF - 10 rounds
10.	Maximum distance of handgun and magazines from torso	50mm
11.	Rule 5.2.3.1 applies (exception for women)	Yes
12.	Restriction on position of holster and other equipment	Yes. See # 21 bellow
13.	Optical/electronic sights permitted	No
14.	Compensators permitted	No
15.	Ports permitted	No

Notes - special conditions:

16. Only 1911 production type pistols. Must be available to the general public and have their basis in the original 1911 service pistol. Pistols made from components that duplicate the factory originals are acceptable. Factory upgrades such as external extractors, firing pin blocks and other factory installed safety features are permitted.
17. Coned barrels or barrels with flanges are prohibited, except in 1911 compact pistols with a barrel length of 4.2 inches or less.
18. Slides will be in factory configuration or within the specified list of allowed modifications.
19. Frames shall be of steel or other metallic alloy, plastic frames are not allowed.
20. A handgun in its ready condition (See Section 8.1), but unloaded and with an empty magazine inserted, must fit wholly within the confines of a box which has internal dimensions of 225mm x 150mm x 45mm (tolerance of +1mm, -0mm). Note that all magazines must comply, failing which Rule 6.2.5.1 will apply.
21. Neither the handgun, nor any of its attachments, nor any allied equipment (e.g.

magazines or other loading devices), can extend forward of the line illustrated in Appendix F3. Any such items a Range Officer deems not to be in compliance must be safely and promptly adjusted, failing which Rule 6.2.5.1 will apply.

22. Competition holsters of the race gun type are specifically allowed.
23. Reserve
24. Magazines must be of standard length, excluding basepads. Extended magazines and/or modifications to basepads to increase magazine capacity are prohibited.

Permitted modifications :

25. Sights of a post and notch type, including fiber optic front sights (milling of slide related to installation of sights is permitted).
26. Grips (weighted grips not allowed).
27. Internal accuracy work (includes replacement of the barrel with one of factory configuration, the use of Accu-Rails, the use of Spherical Bushings).
28. Internal reliability work.
29. Checker front strap and back strap
30. Checker or square and checker trigger guard
31. Cosmetic checkering/serrating and flat topping of slide to include cocking serrations
32. Extended thumb safety (may be ambidextrous) and beavertail grip safety.
33. Extended magazine release.
34. Full-length guide rods manufactured of material that is no heavier than common steel.
35. Hammer and other trigger action parts to enhance trigger pull, including over travel stops.
36. Beveled magazine well and add-on well extensions.
37. Custom finishes.

Prohibited Modifications or features:

38. Full length dust covers of carbon or stainless steel.
39. Slide lightening. (Removal of metal from the slide is permitted only for the following: front and rear sights, front and rear cocking serrations, and flat topping and serration of the slide)
40. External modifications such as weights or devices to control or reduce recoil.
41. Pistols produced with attachment points for external lights or optics.